IN THE CLAIMS

Please amend the claims as follows:

Claims 1-7 (Canceled).

Claim 8 (Currently Amended): A digital camera comprising:

a photographing unit which picks-up an image and obtains image data;

a storage control unit which stores the image data in the form of an image data file in a predetermined manner in a recording medium;

a reconstruction control unit which reconstructs the image data stored in said recording medium;

an image data processing unit which combines the image data picked-up by said photographing unit and the image data reconstructed by said reconstruction control unit to produce an image data, and makes said recording medium store the produced image data;

a display unit which displays the images;

a display control unit which makes said display unit simultaneously display the image data obtained by said photographing unit for monitoring and the image data reconstructed by said reconstruction control unit, or which makes said display unit display the image data produced by said image data processing unit; and

an operational instruction inputting unit which provides operational instruction signals to said photographing unit, said storage control unit, said image data processing unit, and said display control unit;

wherein said photographing unit includes a plurality of CCDs which simultaneously pick-up an image of same or a plurality of objects and obtain a plurality of image data, said display control unit can make said display unit simultaneously display the plurality of image data obtained by said photographing unit, and said operation instruction signals include

translation instructions input by a user to move a first image with respect to the image data obtained by said photographing unit for monitoring after the first image and the image data obtained by said photographing unit for monitoring are displayed by the display unit, said image data obtained by said photographing unit for monitoring being most recent image data measured by said photographing unit, and

wherein said photographing unit can simultaneously obtain a plurality of images of the same object at different exposure values.

Claim 9 (Original): The digital camera according to claim 8,

wherein said image data processing unit can combine a plurality of image data when simultaneously displaying the plurality of the image data on said display control unit.

Claim 10 (Original): The digital camera according to claim 8,

wherein said image data processing unit can perform color correction for each of the plurality of image data.

Claim 11 (Original): The digital camera according to claim 8,

wherein said photographing unit can simultaneously obtain a plurality of images of the same object at different zooming ratios.

Claim 12 (Original): The digital camera according to claim 8,

wherein said photographing unit can simultaneously obtain a plurality of images of the same object at different shutter speed.

Claim 13 (Canceled).

Claim 14 (Original): The digital camera according to claim 8,

wherein said photographing unit can simultaneously obtain a plurality of images of the same object at different white balance values.

Claim 15 (Canceled).

Claim 16 (Currently Amended): A digital camera comprising:

photographing means for picking-up an image and obtains image data;

storage control means for storing the image data in the form of an image data file in a predetermined manner in a recording medium;

reconstruction control means for reconstructing the image data stored in said recording medium;

image data processing means for combining the image data picked-up by said photographing means and the image data reconstructed by said reconstruction control means to produce an image data, and makes said recording medium store the produced image data;

display means for displaying the image data;

display control means for making said display means simultaneously display the image data obtained by said photographing means for monitoring and the image data reconstructed by said reconstruction control means, or making said display means display the image data produced by said image data processing means; and

operational instruction inputting means for providing operational instruction signals to said photographing means, said storage control means, said image data processing means, and said display control means.

wherein said photographing means includes a plurality of image pick-up means which simultaneously pick-up an image of same or a plurality of objects and obtain a plurality of image data, said display control means can make said display means simultaneously display the plurality of image data obtained by said photographing means, and said operation instruction signals include translation instructions input by a user to move a first image with respect to the image data obtained by said photographing means for monitoring after the first image and the image data obtained by said photographing means for monitoring are displayed by the display means, said image data obtained by said photographing means for monitoring being most recent image data measured by said photographing means, and

wherein said photographing means can simultaneously obtain a plurality of images of the same object at different exposure values.

Claim 17 (Canceled).

Claim 18 (Currently Amended): A method of displaying images obtained by a digital camera, the method comprising:

 $simultaneously\ picking-up\ a\ plurality\ of\ images\ of\ a\ same\ or\ different\ objects\ \underline{at}$ $\underline{different\ exposure\ values\ and\ obtaining\ image\ data;}$

storing the image data in a recording medium;

reconstructing the image data stored in said recording medium;

simultaneously displaying a first image and image data obtained by a photographing unit for monitoring on a display unit, said image data obtained by said photographing unit for monitoring being most recent image data measured by said photographing unit;

translating the first image with respect to the image data obtained by said

photographing unit for monitoring after the first image and the image data obtained by said

photographing unit for monitoring are displayed by the display unit;

combining the picked-up image data and the reconstructed the image data to produce a combined image data, and storing the combined image data in said recording medium; and simultaneously displaying on a display of said digital camera a plurality of images corresponding to the picked-up image data for monitoring and the reconstructed image data, or displaying on a display of said digital camera the combined image data.

Claim 19 (Canceled).

Claim 20 (Currently Amended): A mobile terminal comprising:

- a photographing unit which picks-up an image and obtains image data;
- a storage control unit which stores the image data in the form of an image data file in a predetermined manner in a recording medium;
- a reconstruction control unit which reconstructs the image data stored in said recording medium;

an image data processing unit which combines the image data picked-up by said photographing unit and the image data reconstructed by said reconstruction control unit to produce an image data, and makes said recording medium store the produced image data;

- a display unit which displays the images;
- a display control unit which makes said display unit simultaneously display the image data obtained by said photographing unit for monitoring and the image data reconstructed by said reconstruction control unit, or which makes said display unit display the image data produced by said image data processing unit; and

an operational instruction inputting unit which provides operational instruction signals

to said photographing unit, said storage control unit, said image data processing unit, and said

display control unit;

wherein said photographing unit includes a plurality of CCDs which simultaneously

pick-up an image of same or a plurality of objects and obtain a plurality of image data, said

display control unit can make said display unit simultaneously display the plurality of image

data obtained by said photographing unit, and said operation instruction signals include

translation instructions input by a user to move a first image with respect to the image data

obtained by said photographing unit for monitoring after the first image and the image data

obtained by said photographing unit for monitoring are displayed by the display unit, said

image data obtained by said photographing unit for monitoring being most recent image data

measured by said photographing unit, and

wherein said photographing unit can simultaneously obtain a plurality of images of

the same object at different exposure values.

Claims 21-36 (Canceled).

Claim 37 (Previously Presented): A digital camera comprising:

a photographing unit which picks-up a first and a second image and obtains first and

second image data;

a storage control unit which stores the first and second image data in the form of

image data files in a predetermined manner in a recording medium;

a reconstruction control unit which reconstructs the first and second image data stored

in said recording medium;

an image data processing unit which combines the first and second image data pickedup by said photographing unit and the image data reconstructed by said reconstruction control unit to produce an image data, and makes said recording medium store the produced image data;

a display unit which displays the images;

a display control unit which makes said display unit simultaneously display image data obtained by said photographing unit for monitoring and the image data reconstructed by said reconstruction control unit, or which makes said display unit display the image data produced by said image data processing unit; and

an operational instruction inputting unit which provides operational instruction signals to said photographing unit, said storage control unit, said image data processing unit, and said display control unit;

wherein said photographing unit includes a plurality of CCDs which simultaneously pick-up an image of same or a plurality of objects and obtain a plurality of image data, said display control unit can make said display unit simultaneously display the plurality of image data obtained by said photographing unit, and said operation instruction signals include translation instructions input by a user to move first image data obtained by said photographing unit for monitoring with respect to second image data obtained by said photographing unit for monitoring after the first image data and the second image data are displayed by the display unit, said first image data obtained by said photographing unit for monitoring being most recent image data measured by a first CCD in said photographing unit and said second image data obtained by said photographing unit for monitoring being most recent image data measured by a sid photographing unit for monitoring being most recent image data measured by a second CCD in said photographing unit.

Claim 38 (Previously Presented): A method of displaying images obtained by a digital camera, the method comprising:

simultaneously picking-up a plurality of images of a same or different objects and obtaining image data;

storing the image data in a recording medium;

reconstructing the image data stored in said recording medium;

simultaneously displaying first image data obtained by a photographing unit for monitoring and second image data obtained by a photographing unit for monitoring on a display unit, said first image data obtained by said photographing unit for monitoring being most recent image data measured by a first CCD in said photographing unit and said second image data obtained by said photographing unit for monitoring being most recent image data measured by a second CCD in said photographing unit;

translating the first image data with respect to the second image data after the first image data and the second image data are displayed by the display unit;

combining the picked-up image data and the reconstructed the image data to produce a combined image data, and storing the combined image data in said recording medium; and simultaneously displaying on a display of said digital camera a plurality of images corresponding to the picked-up image data for monitoring and the reconstructed image data, or displaying on a display of said digital camera the combined image data.